

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
27 January 2005 (27.01.2005)

PCT

(10) International Publication Number
WO 2005/008583 A3

(51) International Patent Classification⁷: G06T 7/20, 11/00

(21) International Application Number:
PCT/IL2004/000632

(22) International Filing Date: 14 July 2004 (14.07.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/488,382 21 July 2003 (21.07.2003) US

(71) Applicant (for all designated States except US): PAIEON
INC. [US/US]; 747 3rd Avenue, New York, New York
10017-2803 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): ZARKH, Michael

[IL/IL]; 9 Oranim Street, 54052 Givat Shmuel (IL).
KLAIMAN, Moshe [IL/IL]; 21/2 Harava Street, 70700
Gedera (IL).


(74) Agent: REINHOLD COHN AND PARTNERS; P.O.
Box 4060, 61040 Tel Aviv (IL).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

[Continued on next page]

(54) Title: METHOD AND SYSTEM FOR IDENTIFYING AN OPTIMAL IMAGE WITHIN A SERIES OF IMAGES THAT
DEPICT A MOVING ORGAN



(57) Abstract: A method and system for quantifying a cyclic motion within a series of images depicting a moving object subject to composite motion containing a cyclic component and a non-cyclic component of lower frequency than the cyclic component. Composite motion is computed. The non-cyclic component is computed as the integral of motion over a motion cycle. The non-cyclic component is subtracted from the composite motion so as to obtain the cyclic component.

BEST AVAILABLE COPY

WO 2005/008583 A3

INTERNATIONAL SEARCH REPORT

International Application No

PCT/IL2004/000632

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 G06T7/20 G06T11/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G06T G01R

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ, INSPEC, COMPENDEX, IBM-TDB, BIOSIS, EMBASE

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 885 594 A (MEDINOL LTD) 23 December 1998 (1998-12-23)	1,2, 5-10,12, 13,16-23
A	abstract page 2, line 42 - line 50 page 4, line 20 - page 5, line 23 page 7, line 30 - line 45 page 10, line 38 - line 44 page 13, line 22 - page 15, line 14 figures 2,9 ----- -/--	3,4,11, 14,15



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

Z document member of the same patent family

Date of the actual completion of the international search

30 September 2004

Date of mailing of the international search report

31.01.2005

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Engels, A

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. claims: 1-23

processing a series of images depicting a moving object
subject to composite motion for extracting a cyclic motion
component;

2. claims: 24-28

analysis of a graphical representation of a cyclic motion
for identifying those images in a series of images that
depict an event associated with cyclic motion of a moving
object;

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/IL2004/000632

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0885594	A	23-12-1998	US 5924990 A	20-07-1999
			AT 283497 T	15-12-2004
			AT 236574 T	15-04-2003
			AU 757314 B2	13-02-2003
			AU 7307498 A	14-01-1999
			AU 8032298 A	04-01-1999
			BR 9814778 A	26-06-2001
			CA 2240651 A1	19-12-1998
			CZ 9801901 A3	13-10-1999
			DE 19827460 A1	24-12-1998
			DE 69813087 D1	15-05-2003
			DE 69813087 T2	05-02-2004
			DE 69827857 D1	30-12-2004
			DK 885594 T3	14-07-2003
			EE 9800196 A	15-02-1999
			EP 1227342 A1	31-07-2002
			EP 0885594 A2	23-12-1998
			ES 2192290 T3	01-10-2003
			GB 2326479 A , B	23-12-1998
			WO 9857580 A1	23-12-1998
			IL 125000 A	12-05-2004
			JP 11151246 A	08-06-1999
			NO 982817 A	21-12-1998
			PL 326831 A1	21-12-1998
			PT 885594 T	29-08-2003
			RU 2238041 C2	20-10-2004
			SG 68672 A1	16-11-1999
			SK 87098 A3	14-02-2000
			US 6152878 A	28-11-2000
			US 6095976 A	01-08-2000

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
27 January 2005 (27.01.2005)

PCT

(10) International Publication Number
WO 2005/008583 A2

(51) International Patent Classification⁷: **G06T 1/00**

[IL/IL]; 9 Oranim Street, 54052 Givat Shmuel (IL).
KLAIMAN, Moshe [IL/IL]; 21/2 Harava Street, 70700
Gedera (IL).

(21) International Application Number:
PCT/IL2004/000632

(74) Agent: **REINHOLD COHN AND PARTNERS**; P.O.
Box 4060, 61040 Tel Aviv (IL).

(22) International Filing Date: 14 July 2004 (14.07.2004)

(25) Filing Language: English

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(26) Publication Language: English

(30) Priority Data:
60/488,382 21 July 2003 (21.07.2003) US

(71) Applicant (for all designated States except US): **PAIEON
INC.** [US/US]; 747 3rd Avenue, New York, New York
10017-2803 (US).


(72) Inventors; and

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

(75) Inventors/Applicants (for US only): **ZARKH, Michael**

[Continued on next page]

(54) Title: **METHOD AND SYSTEM FOR IDENTIFYING OPTIMAL IMAGE WITHIN A SERIES OF IMAGES THAT DEPICT
A MOVING ORGAN**



(57) Abstract: A method and system for quantifying a cyclic motion within a series of images depicting a moving object subject to composite motion containing a cyclic component and a non-cyclic component of lower frequency than the cyclic component. Composite motion is computed as well as the non-cyclic component as the integral of motion over a motion cycle. The non-cyclic component is subtracted from the composite motion so as to obtain the cyclic component.

WO 2005/008583 A2

- 1 -

**Method and system for identifying optimal image within a series of images that
depict a moving organ**

FIELD OF THE INVENTION

This invention relates to medical image processing devices.

BACKGROUND OF THE INVENTION

Medical imaging devices are often used to image moving organs. Cardiac image
5 processing devices, in particular, are always used to image moving organs, either the heart
(via ultrasound imaging for example), or the coronaries (via angiography for example).
Many of these imaging processing devices are used to quantify the motion either as an
indication by itself or as part of an image-processing algorithm.

An image processing device for Left Ventricle Analysis is used to evaluate
10 Ejection Fraction, which is the percentage of the blood pumped out during each heartbeat.
Left Ventricle Analysis involves computing the Left Ventricle volume from an angiogram
(taken from a cine-angio sequence of images). The Left Ventricle volume is computed
once for the heart in its systolic phase and once for the heart in its diastolic phase. Ejection
Fraction is estimated from the ratio of these volumes. Identifying the systolic and diastolic
15 images is part of the LVA procedure.

Myocardium thickness and Heart Wall Motion are evaluated from Ultrasound
Images to indicate heart failure conditions. Both procedures, again, involve the
identification of systolic and diastolic instances. Furthermore, quantifying the object's
motion could be directly used for Wall Motion evaluation.

20 Intra-Vascular Ultrasound (IVUS) is a method of evaluating and analyzing
coronary defects by means of inserting an intra-vascular ultrasound device and imaging the
vessel. IVUS measurements include measurements of the luminal vessel area. Estimation
of the luminal area very much depends on the heart phase and results vary for different
images depicting different stages within the cardiac cycle. Again, it is useful to identify the
25 diastolic - or the minimal movement instance - in order to perform measurements on the
optimal image.

- 3 -

SUMMARY OF THE INVENTION

It is an object of the invention to provide a method and system for imaging moving organs and to quantify the organ movements.

The present invention provides several methods and systems that relate to the
5 evaluation of an organ motion.

According to the invention, there is provided a method for quantifying a cyclic motion within a series of images depicting a moving object subject to composite motion containing a cyclic component and a non-cyclic component of lower frequency than the cyclic component, the method comprising:

- 10 (a) computing the composite motion;
- (b) computing the non-cyclic component as the integral of motion over a motion cycle; and
- (c) subtracting the non-cyclic component from the composite motion so as to obtain the cyclic component.

15 The invention provides a novel method of evaluating the cyclic motion of an organ from a series of images of any source and provides implementations of such a method that decrease or eliminate motion artifacts. Specifically, we present a novel method and system for selecting optimal images for the process of 3D reconstruction of the coronaries. We further provide a method and system for replacing the need for ECG
20 Gating by an analysis of the heart movement.

A method for estimating the motion of an organ of a series of images comprises the following operations. A medical imaging device acquires a series of images presenting an organ that is in motion. The motion is either of the organ changing shape (eventually, in a cyclic manner, regaining its original shape) or additionally of the organ changing
25 location within the image (in angiography, for example, it is very common to move the patient's bed while imaging; as a result shifting the coronaries' location within the image). If a non-cyclic component is superimposed on the cyclic motion, the series of images are analyzed to separate the cyclic motion from the non-cyclic motion. Once these two types of motion are separated, the cyclic motion can be quantified. The quantified motion can
30 now be used for direct measurements or can be investigated to identify different events within the motion cycle. In some implementations, this investigation will point to an image that is optimal in the sense that it represents minimal motion and thus yields

- 5 -

DETAILED DESCRIPTION OF EXEMPLARY EMBODIMENTS

General principles

The invention will be described with particular reference to the determination of an optimal image within a series of images depicting heart motion possibly containing
5 "noise" caused, for example, by shifting of the operating table on which a patient is disposed. Before doing so, some general algorithms will first be described.

Fig. 2 is a flow chart showing the principal operations carried out by a method according to the invention for identifying an optimal image from a series of images that depict a moving object.

10 Fig. 3 is a flow chart showing a preferred embodiment of such a method for identifying optimal image from a series of coronary cine-angiography images; this image being the input for a three-dimensional reconstruction of a the coronaries.

A series of images is received as input to from any imaging source. These images depict a moving organ subjected to two types of motions. The first is a cyclic motion of
15 the object itself, meaning that, within a certain time frame, the object restores its original shape and position. The second is the motion of the object within the scene (image), meaning that the object changes position due to change in the imaging position. In the preferred embodiment of this method shown in Fig. 3, the images are a series of coronary angiographic images, obtained during a catheterization procedure. The cyclic motion is the
20 heartbeat and the second motion could be, for example, movement of the C-ARM table, causing a shift of the imaged coronary vessels in the image.

First, the overall motion is computed for all sequence of images, using any method, for example optical flow or phase correlation.

If the cyclic period is unknown, then the cycle period is computed from the
25 overall motion data. One method of doing so is by spectral analysis. The non-cyclic motion is computed, using overall motion and known or computed cycle period. A preferred embodiment of a known cycle period is the period of a cardiac cycle extracted from analysis of the ECG signal.

The non-cyclic motion is subtracted from the overall motion to obtain the cyclic
30 motion. In the preferred embodiment shown in Fig. 3, the heartbeat motion is obtained by subtracting the non-cyclic motion (mainly attributed to movement of the patient's bed) from the overall motion.

- 7 -

this sequence are attributed to the organ's cyclic motion, but are also attributed to other factors.

If only cyclic motion is present, the first and the last images in this sequence must be identical, $IM_1 = IM_{m+1}$.

5 Difference between images representing composite motion can be computed, as known in the art, by, for example, optical flow or by applying phase correlation computation to pairs of successive images IM_i and IM_{i+1} , $i \in \{1..m\}$. The result of this computation (for example the result of phase correlation) is described dX_i , dY_i and ρ_i , where dX_i and dY_i are the shift between images (assuming a substantial part of the same
10 pattern is present in both images) in X and Y axes respectively and ρ_i is the correlation grade. ρ_i may be used to enhance the further described algorithms.

Let us define and compute the motion integration as:

$$\begin{bmatrix} X_1 \\ Y_1 \end{bmatrix} = \begin{bmatrix} 0 \\ 0 \end{bmatrix}$$

$$\begin{bmatrix} X_{i+1} \\ Y_{i+1} \end{bmatrix} = \begin{bmatrix} X_i \\ Y_i \end{bmatrix} + \begin{bmatrix} dX_i \\ dY_i \end{bmatrix}$$

15 meaning that in the first image, the motion integral is equal to zero. The motion integral for image $i+1$ is equal to the motion integral for image i plus shift between images i and $i+1$, as computed by the phase correlation.

It is mathematically understandable that the integration of a cyclic motion, from image IM_1 to IM_{m+1} , is zero – if an object starts and ends in the same position, then the
20 integration of the object movements (on X and Y axis) is zero (as shown in Fig. 1). Thus, if only cyclic motion is present, $(X_{m+1}, Y_{m+1}) = (X_1, Y_1) = (0, 0)$.

Let (X_{NC}, Y_{NC}) be the integral of the non-cyclic motion,

$$(X_{NC}, Y_{NC}) = (X_{m+1}, Y_{m+1}),$$

25 This means that, given that the integral of cyclic motion is 0, (X_{m+1}, Y_{m+1}) represent the residual motion that is attributed to non-cyclic movement.

Assuming non-cyclic motion is consistent, or at the least that its frequency is lower than the cyclic motion frequency, we can subtract this motion from the overall
30 motion:

$$(X_i^*, Y_i^*) = (X_i, Y_i) - (X_{NC}, Y_{NC}) * (i-1)/m, \quad i=1, 2, \dots, m+1.$$

- 9 -

$$D_{LM,E} = \max \{D_{i,E}\} \text{ for all } i=1..m+1.$$

We can relieve the requirement for knowing in advance an approximation for the least motion image by means of direct computation. If indeed the least motion instance is not unique, we can use heuristic criteria for distinction. For example, within a sequence of angiograms, depicting a cardiac cycle, it is easy to distinguish between the end-systole instance and the end-diastole instance, both representing least motion, since the end-diastole instance is identified by presenting the coronaries in maximal spreading, while the end-systole instance is identified by presenting the coronaries in minimal spreading.

Preferred Embodiment.

We suggest a preferred embodiment for an application of three-dimensional reconstruction of coronary vessels from a procedure of conventional angiography. In order to reconstruct a three-dimensional image of the arteries, it is necessary to obtain at least two two-dimensional images of the arteries in the same phase of the heartbeat, for example at end-diastole. Therefore, image acquisition is usually synchronized to an ECG signal. This procedure involves simultaneous recordings of the video signal from the X-ray camera and the patient's ECG signal. We present here a novel method for identifying the end-diastole instance, equivalent to ECG-gating, without relying solely, if at all, on the ECG signal.

Let $IM_1, IM_2 \dots IM_n$ be n images of a catheterization-acquired run.

Let m be the number of frames per cardiac cycle, either known in advance or computed as detailed in the above-described method for estimating the organ's motion.

Let IM_k be the approximate location of end-diastolic frame within the cycle, either known in advance or heuristically identified as detailed in the above-described method for obtaining the least motion image.

$IM_{k-m/2}, IM_{k-m/2+1}, IM_{k-m/2+1} \dots IM_{k-m/2+m}$ form a full cardiac cycle (for the sake of simplicity, let us presume that m is an even number). Differences between frames in this sequence are attributed to heart motion, but are also attributed to bed motion, iodine propagation and several other reasons. If only heart motion were present, the first and the

- 11 -

Let:

$$D_{i,j} = \sqrt{(X_i - X_j)^2 + (Y_i - Y_j)^2}$$

We can determine the end-systole point S , which is the one most distant from the approximated end-diastole point, meaning:

5 $D_{S,m/2+1} = \max \{D_{i,m/2+1}\}$

Minimum motion point – end-diastole, ED - is determined as most distant from systole point:

$$D_{S,ED} = \max \{D_{S,j}\}.$$

10 Selecting the IM_{ED} image per sequence of cine-angio images for the process of three-dimensional reconstruction will provide the optimal result, in terms of accuracy and precision, for the reconstruction and for vessel analysis.


In the method claims that follow, alphabetic characters and Roman numerals used to designate claim steps are provided for convenience only and do not imply any
15 particular order of performing the steps.

It will also be understood that the system according to the invention may be a suitably programmed computer. Likewise, the invention contemplates a computer program being readable by a computer for executing the method of the invention. The invention further contemplates a machine-readable memory tangibly embodying a program of
20 instructions executable by the machine for executing the method of the invention.

- 13 -

11. The method according to claim 10, wherein the selected image is closest to a predetermined approximation.
12. The method according to claim 10 or 11, wherein the event is least motion.
13. The method according to claim 12, for selecting angiographic images to participate in three-dimensional reconstruction of coronary vessels.
14. The method according to claim 13, including deriving cycle period and approximation for least-motion image from an analysis of an ECG signal.
15. The method according to claim 13 or 14, including distinguishing the end-diastole instance from the end-systole instance by the state of coronary vessel – maximal spreading versus minimal spreading, respectively.
16. The method according to any one of claims 5 to 15 when used for selecting optimal image or images for QCA analysis.
17. The method according to any one of claims 5 to 15 when used for selecting optimal image or images for IVUS analysis.
18. The method according to any one of claims 5 to 15 when used for selecting optimal image or images for LVA analysis.
19. The method according to any one of claims 5 to 15 when used for selecting optimal image or images for Wall Motion analysis.
20. The method according to any one of claims 5 to 15 when used for CT reconstruction.
21. The method according to any one of claims 5 to 15 when used for MRI reconstruction.
22. The method according to any one of claims 5 to 15 when used for PET reconstruction.
23. A system for quantifying a cyclic motion within a series of images depicting a moving object subject to composite motion containing a cyclic component and a non-cyclic component of lower frequency than the cyclic component, the system comprising:
a composite motion unit computing the composite motion,

1/3



From point	To point	dX	dY	X	Y
0	1	1	1	1	1
1	2	1	0	2	1
2	3	1	0	3	1
3	4	1	-1	4	0
4	5	0	-1	4	-1
5	6	0	-1	4	-2
6	7	-1	-1	3	-3
7	8	-1	0	2	-3
8	9	-1	0	1	-3
9	10	-1	-1	0	-4
10	11	-1	0	-1	-4
11	12	0	1	-1	-3
12	13	0	1	-1	-2
13	14	1	1	0	-1
14	0	0	1	0	0

FIG. 1

3/3




FIG. 3